

Low Viscous Bituminous Primer

DESCRIPTION

TIKI PRIME S is a Ready to use Single Component Quick Drying Low Viscosity Primer in Liquid Form. It is prepared using Special Grade Bitumen under Controlled Condition in Refined Solvent.

USES

It is used as Primer on Concrete, Masonry, Metal, Asbestos Sheet, Wood and Stone Surfaces for Sealing Substrate Pores and Promote Adhesion of Bitumen Based Waterproofing Systems, whether Liquid, Felts or Membranes with the Substrate.

ADVANTAGES

- High Penetrating Power Provides Excellent Adhesion to the Substrate
- Low Viscosity – Ease of Application
- Good Resistance to Mild Acids/Bases, Salt Solution
- High Resistance to Freeze Thaw Cycles
- No Heating Required – User Friendly
- Forms Water Impermeable Film
- Improves Adhesion of Bituminous Waterproofing Systems with Substrate
- Binds left over Dust Particles during Substrate Preparation Increasing Bond
- Quick Drying and Bond Development compared to Water Based Primer

APPLICATION

SURFACE PREPARATION

The surface should be thoroughly cleaned to remove loose dust, foreign particles, rust, laitance, oil and other contaminants.

APPLICATION INSTRUCTIONS

Apply **TIKI PRIME S** using Brush or Spray Gun @ 4 to 6 m²/Ltr. per coat depending upon the Porosity of the Surface uniformly wetting and covering entire surface

Never apply **TIKI PRIME S** on Wet Surface or when it is raining

Never use **TIKI PRIME S** as Waterproof Coating.

Allow the **TIKI PRIME S** to dry completely, before proceeding for installation of Bituminous Waterproofing Systems.

PROPERTIES

TECHNICAL DATA	VALUE
Specific Gravity @ 25°C	0.90 ± 0.05
Viscosity in Seconds by Standard Tar Viscometer of 4mm Orifice@25°C	4 to 24
Distillation Fractions % by Volume Up to 225°C Min.	35
Up to 360°C Max.	65
Flash Point by Pensky Martin Closed Cup	40°C Min.
Test on Residue from Distillation up to 360°C a) Ductility @ 27°C	3cm Min.
b) Penetration @ 25°C, 100gm, 5 Sec	20 to 50 dmm
c) Matter Soluble in Carbon Di Sulphide or Carbon Tetra Chloride or Trichloroethylene by Weight	99% Min.

CLEAN UP

Use Solvents for cleaning equipment and tools immediately after applying **TIKI PRIME S**.

SUPPLY

TIKI PRIME S is supplied in standard pack sizes of **20 Ltrs.** and **200 Ltrs.** Capacity Tins / Drums.

STORAGE

TIKI PRIME S must be stored above 5°C. Store under the shed & protect from extremes of temperature. Keep container close when not in use.

SHELF LIFE

Shelf life is 12 months when stored as above and in Original Sealed Container. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage of **TIKI PRIME S** to avoid contact with eyes, mouth, skin and foodstuffs until product fully cured or dried.

Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children, animals and direct sources of high temperatures, naked flame and sparks. Reseal containers after use. Do not reuse containers for storage of consumable item.

VERSION: R3, 202203

Disclaimer: The technical information, and, in particular, the recommendations relating to the application and end-use of Tiki Tar Danosa (TIKIDAN) products, are given in good faith based on TIKIDAN's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with TIKIDAN's recommendations. The information herein is of a general nature and no assumption can be made as to a product's suitability for a particular use or application and no warranty in respect of merchantability or of fitness for a particular purpose can be inferred from this information. The user alone is fully responsible for the product's suitability for the intended application and purpose. TIKIDAN reserves the right to change the properties of its products.

Note: Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

TIKIDAN (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,
Maharashtra, India. T: +91 22 4126 6699
E: info@tikidan.in | W: www.tikidan.in



ISO 9001:2015